



Lifeguard® **LOW SHEEN™** **JOINT STABILIZING SEALER®**

[Click to View larger](#)

[Back To **TECH INFO**](#)

PREFERRED APPLICATION TOOLS:

1. Low Pressure Sprayer with fan tip. Do not exceed 50 PSI.
2. Natural Bristle Brush.
3. Nap Roller: 3/8 or 3/4"

APPLICATION TECHNIQUES:

SPRAYER: Pass nozzle about 8 to 12 inches from the surface in straight, short swipes. Allow the first coat to dry for 15 minutes. A second coat may be applied to achieve higher sheen.

IMPORTANT : This product dries quickly when sprayed. To remove any surface imperfections, dampen a 1/4" roller with Lacquer Thinner. Slowly roll the area and repeat if needed.

APPLICATION GUIDELINES:

1. Apply one coat of product to a small, inconspicuous area. If the product does not penetrate or produces results in any way which are not satisfactory to you, discontinue its use and contact a Lifeguard Customer Service representative. Wait a least 24 hours to determine compatibility.
2. Avoid application on **DIRTY** or **WET** surfaces. Do not apply to previously painted, sealed or stained surfaces. Protect freshly coated surfaces from dust, rain and traffic while drying.
3. Power Washing with at least 2000 psi is recommended. General cleaning can be done by using Lifeguard Paver Cleaner & Brightener in conjunction with a power-washer. For stains and efflorescence use Lifeguard Rust or Efflorescence Remover. Read product container for specific instructions and cautions.
4. Allow at least 48 hours of drying time after power washing.
5. Be sure to mask off glass, plastic and metal. Protect plants, grass and other materials by shielding or covering.
6. The joint sand needs to be level with the bottom of the chamfer on beveled pavers. The sand must be 1/8" below the surface on non-beveled or tumbled pavers.

DRYING TIME:

1. Allow at least 12 hours for foot traffic.
2. 24 hours for water exposure.
3. 72 hours for vehicle traffic.

CLEAN UP:

1. Cleans up easily with Lacquer Thinner.
2. Equipment must be thoroughly cleaned after use.

COVERAGE RATES: *ESTIMATED COVERAGE

Concrete Pavers/Tile: 50-75 sq.ft/gal

Clay Pavers/Tile: 100-125 sq.ft/gal

*These estimates may vary due to porosity.

IMPORTANT: Read product container before starting project.